

SR539

FILM ILLUMINATOR

- DIMENSIONS - 27 7/8" [708mm] L, 20 1/2" [521mm] H
- FRAME - 18 GA. STAINLESS STEEL
- BALLASTS - ELECTRONIC, CLASS P, LOW LEAKAGE CURRENT
- LINE CORD - GROUNDED CHASSIS WITH 8-FOOT, 3-WIRE LINE CORD NEMA 5-15P, 2-POLE, 3-WIRE GROUND
- LAMP - F15T8/D DAYLIGHT FLUORESCENT LAMP
- ELECTRICAL
 - 2-LAMP SERIES, 120V/ 60 Hz, .60 AMPS PER SECTION
 - 3-LAMP SERIES, 120V/ 60 Hz, .85 AMPS PER SECTION
 - 4-LAMP SERIES, 120V/ 60 Hz, .91 AMPS PER SECTION
- FILM GRIP - SELF ADJUSTING ROLLER-GRAVITY GRIP TO PREVENT SCRATCH OR TEAR
- SWITCH - STANDARD SWITCH 2-POSITION ON/OFF ROCKER SWITCH
- WEIGHT - 33 LB. [15kg] APPROXIMATELY

OPTIONS:

- FILM ACTIVATED SWITCH, 3-POSITION ON/OFF/AUTO ROCKER SWITCH
- DUAL INTENSITY SWITCH, HIGH/LOW
 - 3 & 4-LAMP SERIES ONLY
- MASTER SWITCH, ON/OFF CONTROL FOR ENTIRE FIXTURE
- ALTERNATE ELECTRICAL

CONTACT CSI/JEWETT FOR CUSTOM SPECIFICATIONS OR
OPTIONAL
PANEL QUANTITIES AND ARRANGEMENTS